

Package: DPQBootstrap (via r-universe)

June 8, 2026

Title Dirichlet Quantile Bootstrap for Time Series

Version 0.1.1

Maintainer Ahmed Hamimes <ahmed.hamimes@univ-constantine3.dz>

Description Provides a Dirichlet-based quantile bootstrap method for time series with rank-preserving reconstruction and averaged bootstrap samples. The package generates bootstrap trajectories, a mean bootstrap series, and uncertainty intervals for time series resampling.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

Imports stats, rlang

Suggests ggplot2

NeedsCompilation no

Author Ahmed Hamimes [aut, cre]

Repository <https://ahmedhamimes.r-universe.dev>

Date/Publication 2026-05-05 20:36:29 UTC

RemoteUrl <https://github.com/cran/DPQBootstrap>

RemoteRef HEAD

RemoteSha 8b0d29cd5d98b23c0792c2a81d8faba5b5879aa7

Contents

dpq_bootstrap	2
plot_dpq	2
Index	4

 dpq_bootstrap

DP-Quantile Bootstrap for Time Series

Description

Generate bootstrap time series using a Dirichlet-based quantile bootstrap with rank-preserving reconstruction.

Usage

```
dpq_bootstrap(x, R = 500, alpha = 1, seed = NULL)
```

Arguments

x	Numeric vector. Original time series.
R	Integer. Number of bootstrap replications.
alpha	Positive numeric. Dirichlet concentration parameter.
seed	Optional seed.

Value

A list containing bootstrap samples, mean series, quantiles and ranks.

Examples

```
x <- c(120, 125, 118, 130, 128, 135, 140, 138, 145, 150)
res <- dpq_bootstrap(x, R = 20, alpha = 1, seed = 123)
res$mean_series
dim(res$samples)
```

 plot_dpq

Plot DP-Quantile Bootstrap Result

Description

Plot DP-Quantile Bootstrap Result

Usage

```
plot_dpq(object, dates = NULL, interval = "50")
```

Arguments

<code>object</code>	Object returned by <code>dpq_bootstrap()</code> .
<code>dates</code>	Optional vector of dates.
<code>interval</code>	Character. Either <code>'50'</code> or <code>'95'</code> .

Value

A ggplot object.

Examples

```
x <- c(120, 125, 118, 130, 128, 135, 140, 138, 145, 150)
res <- dpq_bootstrap(x, R = 20, alpha = 1, seed = 123)
if (requireNamespace('ggplot2', quietly = TRUE)) {
  plot_dpq(res, interval = '50')
}
```

Index

`dpq_bootstrap`, [2](#)

`plot_dpq`, [2](#)